

125 Series GPSDO Product Comparison

| Model Number | 1PPS | Holdover (excludes aging) | Jitter (@10Hz) | Voltage | Temp Range | Lock to External 1PPS | Lock to External 10MHz | Wander Generation |
|--------------|------|------------------------------|-------------------|--------------|-------------|--------------------------|---------------------------|-------------------|
| Wi125 | Yes | ≤ 600 PPB | N/A | 3.3 Vdc | -30 to 80°C | No | No | N/A |
| FTS125-CTV | Yes | ≤ 600 PPB | -70dBc | 3.3 Vdc | 0 to 70°C | Yes | Yes | ITU-T G.811 |
| FTS125-COV | Yes | ≤ 25 PPB | -70dBc | 3.3 Vdc | 0 to 70°C | Yes | Yes | ETSI-PRC |
| FTS125-COO | Yes | ≤ 25 PPB | -105dBc | 3.3 Vdc | 0 to 70°C | Yes | Yes | ETSI-PRC |
| FTS250 | Yes | ≤ 320 PPB | -90dBc | 3.3, 5.0 VDC | -40 to 85°C | Yes | Yes | ITU-T-G.811 |
| FTS375 | Yes | ≤ 25 PPB | -115dBc | 3.3, 5.0 VDC | 0 to 70°C | Yes | Yes | ETSI-PRC |
| FTS500 | Yes | ≤ 25 PPB | -115dBc | 8 - 24 VDC | 0 to 70°C | Yes | Yes | ETSI-PRC |

All Units are Fixed Position. Contact Connor-Winfield Sales for mobile application models.